

Mechanism and mitigation of earth fissure in China


Chang'an University Jianbing Peng

e-mail:dicexy_1@chd.edu.cn


April. 2017

6: Failure modes of high-speed railway and metro. Engineering construction design.

The intersections of Xi'an Metro and ground fissures up to hundreds, which makes a serious threat on Xi'an metro construction.



- 1. fortified length?
- 2. Failure modes?
- 3. Countermeasures?



The calculation formula and design values of parameters for tunnel passing through the ground fissure active zones were put forward.





Longitudinal fortified length of tunnel:



$$a'b = oa' \cdot \sin(90^0 - \theta) = \frac{H}{tg\beta} \cos \theta$$

$$ab = oa' \cdot \cos(90^{\circ} - \theta) = \frac{H}{tg\beta} \sin \theta$$



(horizontal)

(longitual)

$$L = L_1 + L_2 = \frac{D_1}{\sin \theta} + \frac{D_2}{\sin \theta} = (D_1 + D_2) / \sin \theta$$


Average vertical dislocations in design lifetime of 100 years (cm)


地裂缝名 称	f ₂	f ₃	f 朝阳门外	f ₄	f ₅	f ₆	f ₇	f ₈	f ₉	f ₁₀	f ₁₁	f ₁₂
地铁2号线	225	300			450	500	300	300	300	225	450	150
地铁1号线		500/150	150	150	600	600/300						

Large-scale model test of ground fissures was developed, and the mechanism as well as failure process on metro tunnel was simulated.











Large-scale model test of open excavation metro tunnel passing through the active ground fissure (1:5)






Annular cracks occurred on the footwall.

Large-scale model test of horseshoe tunnel passing through the active ground fissure (1:5)







Annular and longitudinal cracks occurred on the hanging wall and footwall

Large-scale model test of shield tunnel passing through ground fissure (1:5)








Annular and longitudinal cracks occurred on the hanging wall and footwall

Metero tunnel passing through the ground fissure with a small angle.




Location diagram of metro line 3 and ground fissures.

Large-scale model test of horseshoe tunnel passing through the active ground fissure with a small angle




Annular, longitudinal, and torsional cracks

The tunnel tensed near the footwall of the ground fissure, and deformed asymmetrically with the characteristic of torsion.



Axial strain curve of the concrete (No.2) Axial strain curve of the concrete (No.10)

Numerical simulation on metro tunnel passing through the ground fissure with a small angle



发现对缝和骑缝等两种变形缝设置都是可行的

4 metro tunnel deformation failure modes caused by earth fissure.



Tensile failure of integral lining



Shear failure of tunnel




Tensile-torsional failure of integral lining




Torsional-shear failure of tunnel

Structural measures for the metro tunnel to adapt to the ground fissure deformation

Verification model test of Segmented box tunnel (1:5)









Large-scale model test of Segmented horseshoe tunnel (1:5)









发现分段设缝的马蹄形隧道为穿越地裂缝带的首选结构型式

How to segment: segmented tunnel was used to adapt to the deformation of ground fissure.


when $0 \le 45^{\circ}$, the length of segmented tunnel (crossing the ground fissure) was 15m;



when $\theta > 45^{\circ}$, the length of segmented tunnel (crossing the ground fissure) was 20m.




4 kinds of structural countermeasures






Setting up deformation joints in segmentation on the tunnel








Enlarged Cross-section

Track adjustment


Waterproof structure



Structural measures of metro tunnel against ground fissure in Xi'an

The above results have been applied to the design and construction of Xi'an metro and will support the construction of other metro lines in Xi'an.

Disaster preventation and treatment issue was solve in underground pipeline, and became a demostration project of underground space development in Xi'an.







Distribution of earth fissure and underground pipeline

Physical simulation




主要创新成果

中国多条高速铁路面临地裂缝威胁,如何保障其运营安全



Datong-Yuncheng high-speed railway has 36 intersections with the ground fissures.






The maximum vertical displacement=4cm/a, the designed differential settlement of high-speed railway basement≤5mm, and the differential settlement of bridges≤5m.













Activity rate 4 cm/a

Large scale model test of high speed railway subgrade affected by the activity of ground fissure (1:5, for the first time)














The formation and evolution process was reappeared via large-scale physical model tests.





Field discussion

Cavity of piles

Pressure of CFG-pile tip








Failure of basement




Failure of subgrade


Numerical simulation confirmed the deformation and failure mechanism




Cavity of piles



Simulation of geotechnical grille



Stress of CFG-pile



Deformation of concrete floor

Large scale model tests, combined with numerical simulation, disclosed the influence ground fissure had on high-speed railway bridge.





图 10.76 道床板、轨枕、轨道施工图型


Cracks appeared on the slab when the settlement = 3cm





The maximum cavity displacement = 20%, and the maximum opening width = 5%.

图 10.77 试验模型完工图↩

Deformation and failure process of the bridge was simulated by numerical simulation.







(a) 整体变形云图

(b) 上盘桥墩垫板处局部变形云图→